





## Water Amplifying Shower Head Installation Instructions

**Tools needed:** Wrench (to remove old shower head) and plumber tape.


- 1** Remove old shower head from shower arm.




- 2** Remove any excess materials left on the threads of the shower arm and wrap plumber tape around the threads.



- 3** Hand tighten the new shower head to the shower arm by turning clock wise. Turn on the water and check the system for leaks.



- 4** To adjust the water flow, set desired water flow by turning the knob.



**For surface cleaning of parts,** use water and soap. Dry with a soft cloth.

*Note: Any other cleaning product not specifically designed for cleaning plastic or metal surfaces may damage the finish.*

**Lifetime Warranty** Delta Faucet warrants to the owner of this product that the product is free from defects in material or workmanship for the period stated above from the date of purchase. Return it to the dealer where purchased or return the product, postage prepaid (we recommend United Parcel Service) to Alsons Corporation, 550 Uran Street, Hillsdale, MI 49242. We will repair or replace, at our discretion, at no charge. This warranty gives you specific legal rights. You may also have other rights that vary where you reside.

*If this product malfunctions or becomes damaged, stop use and return it to Master Plumber for examination and/or repair.*


For assistance with problems with installation: Call toll free 1-800-421-0001, 8:00 a.m. to 6:00 p.m. Eastern Standard Time Monday - Friday.




## Water Amplifying Shower Head Installation Instructions

**Tools needed:** Wrench (to remove old shower head) and plumber tape


- 1** Remove old shower head from shower arm.




- 2** Remove any excess materials left on the threads of the shower arm and wrap plumber tape around the threads.



- 3** Hand tighten the new shower head to the shower arm by turning clock wise. Turn on the water and check the system for leaks.



- 4** To adjust the water flow, set desired water flow by turning the knob.



**For surface cleaning of parts,** use water and soap. Dry with a soft cloth.

*Note: Any other cleaning product not specifically designed for cleaning plastic or metal surfaces may damage the finish.*

**Lifetime Warranty** Delta Faucet warrants to the owner of this product that the product is free from defects in material or workmanship for the period stated above from the date of purchase. Return it to the dealer where purchased or return the product, postage prepaid (we recommend United Parcel Service) to Alsons Corporation, 550 Uran Street, Hillsdale, MI 49242. We will repair or replace, at our discretion, at no charge. This warranty gives you specific legal rights. You may also have other rights that vary where you reside.

*If this product malfunctions or becomes damaged, stop use and return it to Master Plumber for examination and/or repair.*

For assistance with problems with installation: Call toll free 1-800-421-0001, 8:00 a.m. to 6:00 p.m. Eastern Standard Time Monday - Friday.